WRB HE Single-Sided Digital Kiosk

Digital Kiosk × 75", Windows 11

16GB + 512GB | 75" | Windows 11 | IP65 | MOQ: 500 units

TECHNICAL SPECIFICATIONS

Display: 75-inch TFT-LCD, 3840×2160, display area 1649×930mm

Panel: Original Samsung, LG, AUO or BOE, A-level

Brightness: 2500 nits standard maximum; brightness sensor with automatic adjustment to daylight

Contrast: 1200:1

View Angle: 178°/178° (H/V)

Life Time: > 50,000 hours

Glass: Anti-glare 5mm, 97% light transmittance, reflectivity below 3%, laminated explosion-proof membrane; IK10 vandal-proof protective glass

Shell: Galvanised steel with outdoor powder coating, anti-corrosion for 10+ years; grey and black

Processor: Intel i3, 6th generation

OS: Windows 11

Memory: DDR4 16GB + 512GB SSD

Network: Gigabit Ethernet LAN, WiFi 6 with internal antennas

Interfaces: HDMI out ×1, USB ×4, LAN ×1, VGA ×1

Speakers: 2 × 10W

Air Quality Sensing: Detects and reports CO2, PM2.5, PM5, humidity and temperature

Cooling: Built-in air conditioning

Lighting: RGB LED background light with sequenced changes

Power: AC 110V - 240V, 50/60Hz; 3200W consumption; industrial-grade power board

Protection: Leakage, lightning and internal surge protection

Energy Timer: Internal timer switches the kiosk on and off at set times

Security: Mount for a CCTV camera on top to monitor the whole kiosk (WiFi 6, Full HD, wide angle)

Operating Temp.: -40°C to 55°C

Humidity: 10% - 85%

OPERATIONAL NOTES

- OSD Language: English, Chinese, French, German, Italian, Spanish,Arabic
- Accessories: Power Cable, Allen Key

About Us

WRB Global specialises in mission-critical aspects of aid and development procurement, from reliable endpoint hardware to cybersecurity to power infrastructure.

Biometric Registration | Industrial Power Generation | Secure Elections Printing | ID Issuance and Verification | Rapid Response Delivery via Charter

wrb-global.com/contact.html

+27 10 158 4362